

T7E Terminal

The Standard for Credit and Debit Card Terminals

Hypercom's® T7E Terminals create the industry standard with a sensible user interface and high performance communications.

Product Highlights:

- ✓ 35 key keyboard for single stroke function activation
- ✓ 256K to store more than 1000 transactions
- ✓ Under 10 second dial access response time
- ✓ SDLC multi-protocol support
- ✓ High contrast 2 x 20 backlit LCD display
- ✓ Full track 1 and 2 simultaneous card reader
- ✓ Multi-host applications
- ✓ Dial, LAN or leased line operation



POS payment applications are becoming increasingly complex, as more payment transactions are added. It is important to simplify terminal operation. Hypercom's T7E – with its sensible user interface and high performance communications – is the answer. Its 35 pre-programmed keys allow for single stroke "Hot Key" function activation for a wide range of draft capture, debit and check verification transactions. The T7E also enables entry of alpha data with single keystrokes.

With faster dial access response times and reduced communications costs, the T7E ensures lower operating expenses.

No matter how sophisticated your POS transaction application, the T7E sets the standard in terminal functionality, reliability and ease-of-use. Its sensible user interface and high performance communications, ensures reduced operating costs and improved service quality.



T7E shown in retail situation with PB Printer



The Future of Transaction Technology

1-800-578-2436

2851 W. Kathleen Road, Phoenix, AZ 85023
Tel: (602) 504-5000 • Fax: (602) 504-4578

T7E

Specifications

Protocol	SDLC (Synchronous) and Asynchronous (VISA 1 and 2)
Display	2 x 20 back lit LCD
Keyboard	35 keys
Memory	
EPROM	32K
RAM	256K
Optional	1 MB
Card Reader	Tracks 1 and 2 simultaneous read (Track 3 optional)
Communications	Modem Bell 212A/103, CCITT V.22/V.21, 1200/300bps (2400bps modem optional) LAN, RS485, 2 wire
Power	+24Vdc, 200mA
Auxiliary Ports	
ECR	RS232
PIN Pad	RS422
Parallel Printer	TTL
Peripheral Compatibility	S7C, S7SC, S7GCB, S8 P8S, P8F, P7E, ICE
Dimensions	6" W x 6.75" D x 2.25" H
Weight	1.3 lbs.
Memory/Clock Backup	Lithium battery (5 years)
Operating Temperature	0°C to +45°C (+32°F to +113°F)
Clock/Calendar	Host controlled
Relative Humidity	15-85 percent, noncondensing
ESD Resistance	12,000V
Options	Memory upgrades to 1MB 2400 baud modem Track 3 reader Graphics display (T7GE) QWERTY keyboard (T7Q)
Reliability	
MTBF	95,000 hours
Key Life	350,000 operations
Card Reader	400,000 reads
Warranty	5 Year Terminal Warranty



Corporate Office

2951 West Kathleen Rd. • Phoenix, Arizona 85053
Tel: (602) 504-5000 • Fax: (602) 504-4578

1-800-578-2436

International Regional Offices

Hypercom Asia / Pacific Rim
Kowloon Bay, Hong Kong
Tel: 852-2561-6800
Fax: 852-2561-5890

Hypercom EMEA
Surrey, England
Tel: 44-1483-718600
Fax: 44-1483-718901

Hypercom Latino America
Miami, Florida
Tel: (305) 477-0315
Fax: (305) 477-4172

Regional Sales Offices

Atlanta, GA
Tel: (770) 641-7117
Fax: (770) 645-4490

Chicago, IL
Tel: (708) 301-6820
Fax: (708) 301-6641

Los Angeles, CA
Tel: (310) 455-0708
Fax: (310) 455-2969

New York, NY
Tel: (516) 676-5779
Fax: (516) 676-5806